Specifications

### **II** CLIPSAL



# Single Switched Socket Outlet, Clipsal Iconic Outdoor, Horizontal, 10A, 250V

O3015-BK

### Main

Range of product	Iconic
Product or component type	Switched socket
Product brand	Clipsal
Assembly Type	Complete product
Control type	On/off switching
Outlet poles configuration	1P + E

### Complementary

<b>Complemental y</b>		
Control type	ON/OFF button Rocker	
Pin number	3	
Number Of Outlets	1	
Socket-outlet type	Single socket-outlet	
Mounting Type	By screws By clipping locks	
Local signalling	Without light indicator	
Installation Type	Surface Wall mounted	
Installation Orientation	Horizontal	
Material	PC (polycarbonate) ABS (acrylonitrile butadiene-styrene) POM (polyoxymethylene)	
Surface finish	Matt	
type of installation	Outdoor	
[Ue] rated operational voltage	250 V AC	
Network frequency	50 Hz	
[In] rated current	10 A	
Clamping connection capacity	3 x 2.5 mm² 2 x 4 mm²	
Depth	70 mm	
Height	85 mm	
Width	115.5 mm	

IP degree of protection	IP54
Product certifications	RCM
Electrical durability	12000 cycles
Ambient air temperature for storage	060 °C
Standards	AS/NZS 3112
relative humidity	1095 %
Ambient air temperature for operation	045 °C

## **Packing Units**

PCE
1
8.7 cm
11.9 cm
8.9 cm
274.0 g
BB2
30
30.9 cm
41.3 cm
45.9 cm
9.22 kg
P06
360
105.0 cm
60.0 cm
80.0 cm
119.14 kg

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

#### 🧭 Environmental footprint

Environmental Disclosure

Product Environmental Profile

#### **Use Better**

⊗ Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

#### Use Again

$^{\circlearrowright}$ Repack and remanufacture	
Circularity Profile	End of Life Information
Halogen content performance	Halogen free plastic parts product
Take-back	No